

TA54 HYDRAULIC TAMPER

STANLEY®



The TA54 Tamper is ideal for soil compaction around utility poles, sign and fence posts. It provides 1,600 blows per minute with a long 2-1/2 inch stroke for optimum compaction.

The long stroke keeps the TA54 above the fill making it easy to reposition the tool.

Only 2 moving parts.

Depending on model the TA54 is furnished with a 3 x 8 inch kidney foot, a 4 or 6 inch diameter round shoe or a 4 x 8 inch rectangular shoe can be ordered as options to the base model.

SPECIFICATIONS

ITEM	
Performance	1,600 Blows Per Minute
Flow Range	3-9 gpm / 11-34 lpm
Pressure	1,000-2,000 psi / 70-140 bar
Weight	25 lb. / 11.3 kg
Length	See Specific Model under Ordering Information
Width	4 in. / 10.2 cm
Handle Length	All Models - 3 ft.
Connection	Adapters or Hoses & Couplers
Hoses	Only with model T54603A
Couplers	1/2 in. SAE O-Ring Port
System Type	HTMA Type I and Type II

Model Numbers

Model	Description
TA54103	Tamper - OC, Kidney Shoe, 71 in. Long, Valve in Handle, Couplers, No Hose Whips
TA54603	Tamper - OC, Kidney Shoe, 69 in. Long, No Valve in Handle, Couplers, No Hose Whips
TA54603A	Tamper - OC/CC, Kidney Shoe, 69 in. Long, In-Line Valve, Hose Whips and Couplers
TA54113	Tamper - Round Shoe, 71 in. Long, Valve in Handle, Couplers, No Hose Whips

TA54 HYDRAULIC TAMPER

STANLEY®

ORDERING INFORMATION

Model	Part No.	Weight	Length w/o Couplers and Hose Whips	Width	Flow Range	Working Pressure	Full Relief Setting	Blows/Minute	Valve	Shoe	Coupler
TA54	TA54103	30 lbs / 13.6 kg	71 in. / 180 cm	4 in. / 10 cm	3-9 gpm / 11-34 lpm	1000-2000 psi / 70-140 bar	2250 psi / 155 bar	1600 bpm	In-handle	Kidney	Yes
	TA54603	30 lbs / 13.6 kg	69 in. / 175 cm	4 in. / 10 cm	3-9 gpm / 11-34 lpm	1000-2000 psi / 70-140 bar	2250 psi / 155 bar	1600 bpm	No Valve	Kidney	Yes
	TA54603A	37 lbs / 17 kg	69 in. / 175 cm	4 in. / 10 cm	3-9 gpm / 11-34 lpm	1000-2000 psi / 70-140 bar	2250 psi / 155 bar	1600 bpm	Remote In-line	Kidney	Yes
	TA54113	30 lbs / 13.6 kg	71 in. / 180 cm	4 in. / 10 cm	3-9 gpm / 11-34 lpm	1000-2000 psi / 70-140 bar	2250 psi / 155 bar	1600 bpm	In-handle	6 in. Round Shoe	Yes

ACCESSORIES

Part	Description
00833	Kidney Shoe
00840	Round Shoe, 6 in. Diameter
01070	Rectangular Shoe
35784	8 ft. Hose (2 Required)
72264	In-Line Valve Assembly OC/CC

Service Tools	
Part No.	Description
021120	Tamper Sleeve Tool
01949	Sleeve Installation Wrench
04337	O-Ring Tool Kit

All Stanley hydraulic tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley hydraulic tools.

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.